

# 2006 Tow

**2WD**=Two-wheel drive

**4WD**=Four-wheel drive

**a4**=Four-speed automatic transmission

**a5**=Five-speed automatic transmission

**AWD**=All-wheel drive

**CV**=Cargo van

**DRW**=Dual rear wheels

**LB**=Longbed

**LWB**=Long wheelbase

**NA**=Not available/not applicable

**PV**=Passenger van

**SB**=Shortbed

**SRW**=Single rear wheels

**SWB**=Short wheelbase

**t**=Towing package required

**TBD**=To be determined (not available at presstime)

**TD**=Turbodiesel

**XLWB**=Extra-long wheelbase

## Acura

Vehicle	Engine	Tow Limit (LB)
MDX	3.5L V-6	4,500/3,500*

\*4,500-Lb boat or 3,500-Lb trailer.

## BMW

Vehicle	Engine	Tow Limit (LB)
X3 2.5i	2.5L I-6	3,500
X3 3.0i	3.0L I-6	3,500
X5 3.0i	3.0L I-6	6,000
X5 4.4i	4.4L V-8	6,000
X5 4.8is	4.8L V-8	6,000

## Buick

Vehicle	Engine	Tow Limit (LB)
Rainier RWD	4.2L I-6	5,800a
Rainier RWD	4.2L I-6	6,300b
Rainier RWD	5.3L V-8	6,700a
Rainier AWD	4.2L I-6	5,600a
Rainier AWD	4.2L I-6	6,100b
Rainier AWD	5.3L V-8	6,600a
Rendezvous	3.5L V-6	3,500t
Rendezvous	3.6L V-6	3,500t
Terraza	3.9L V-6	3,500t

a=3.73:1 axle; b=4.10:1 axle.

## Cadillac

Vehicle	Engine	Tow Limit (LB)
Escalade 2WD	6.0L V-8	7,400
Escalade AWD	6.0L V-8	8,100
Escalade ESV	6.0L V-8	7,800*

Escalade EXT	6.0L V-8	7,500
SRX	3.6L V-6	4,250t
SRX	4.6L V-8	4,250t

\*Platinum Edition rating is 7,200 lb.

## Chevrolet/GMC

### Chevrolet Colorado/GMC Canyon

Vehicle	Engine	Tow Limit (LB)
		Man./Auto
Colorado/Canyon Reg Cab 2WD	2.8L I-4	2,300b/3,300b
Colorado/Canyon Reg Cab 2WD	3.5L I-5	3,200a/4,000a
Colorado/Canyon Reg Cab 2WD	3.5L I-5	3,700b/4,000b
Colorado/Canyon Ext Cab 2WD	2.8L I-4	2,100b/3,100b
Colorado/Canyon Ext Cab 2WD	3.5L I-5	3,100a/4,000a
Colorado/Canyon Ext Cab 2WD	3.5L I-5	3,600b/4,000b
Colorado/Canyon CC 2WD	2.8L I-4	NA/2,900b
Colorado/Canyon CC 2WD	3.5L I-5	NA/4,000a/b
Colorado/Canyon Reg Cab 4WD	2.8L I-4	2,000b/c; 3,000b/c
Colorado/Canyon Reg Cab 4WD	3.5L I-5	3,000a/4,000a/b/c
Colorado/Canyon Reg Cab 4WD	3.5L I-5	3,500b/c; 4,000a/b/c
Colorado/Canyon Ext Cab 4WD	2.8L I-4	NA/2,900b/c
Colorado/Canyon Ext Cab 4WD	3.5L I-5	2,800a/4,000a/b/c
Colorado/Canyon Ext Cab 4WD	3.5L I-5	3,300b/c; 4,000a/b/c
Colorado/Canyon CC 4WD	2.8L I-4	NA/2,700b/c
Colorado/Canyon CC 4WD	3.5L I-5	NA/4,000a/b/c

a=3.42:1 axle; b=3.73:1 axle; c=4.10:1 axle; CC= Crew Cab.

### Chevrolet Equinox, SSR, Uplander

Vehicle	Engine	Tow Limit (LB)
Chevrolet Equinox	3.4L V-6	3,500
Chevrolet SSR	6.0L V-8	2,500

# TOWING GUIDE

Chevrolet Uplander	3.5L V-6	3,500t
Chevrolet Uplander	3.9L V-6	TBD

## Chevrolet Express/GMC Savana

Vehicle	Engine	Tow Limit (Lb)
Express/ Savana 1500 SWB CV 2WD	4.3L V-6	4,300a
Express/ Savana 1500 SWB CV 2WD	5.3L V-8	5,900a/b
Express/ Savana 1500 SWB CV AWD	5.3L V-8	6,500a/b
Express/ Savana 1500 SWB PV 2WD	4.3L V-6	3,900a
Express/ Savana 1500 SWB PV 2WD	5.3L V-8	6,300a/b
Express/ Savana 1500 SWB PV AWD	5.3L V-8	6,100a/b
Express/ Savana 2500 SWB CV 2WD	4.3L V-6	4,600b
Express/ Savana 2500 SWB CV 2WD	4.8L V-8	6,300b
Express/ Savana 2500 SWB CV 2WD	4.8L V-8	7,300c
Express/ Savana 2500 SWB CV 2WD	5.3L V-8	6,600b
Express/ Savana 2500 SWB CV 2WD	6.0L V-8	8,300b
Express/ Savana 2500 SWB CV 2WD	6.0L V-8	10,000c
Express/ Savana 2500 SWB CV 2WD	6.6L TD	10,000b
Express/ Savana 2500 SWB CV AWD	5.3L V-8	6,400b
Express/ Savana 2500 LWB CV 2WD	4.3L V-6	4,400b
Express/ Savana 2500 LWB CV 2WD	4.8L V-8	6,100b
Express/ Savana 2500 LWB CV 2WD	4.8L V-8	7,100c
Express/ Savana 2500 LWB CV 2WD	5.3L V-8	6,400b
Express/ Savana 2500 LWB CV 2WD	6.0L V-8	8,100b
Express/ Savana 2500 LWB CV 2WD	6.0L V-8	10,000c
Express/ Savana 2500 LWB CV 2WD	6.6L TD	10,000b
Express/ Savana 2500 SWB PV 2WD	4.8L V-8	5,800b
Express/ Savana 2500 SWB PV 2WD	4.8L V-8	6,800c
Express/ Savana 2500 SWB PV 2WD	6.0L V-8	7,800b
Express/ Savana 2500 SWB PV 2WD	6.0L V-8	9,800c
Express/ Savana 2500 SWB PV 2WD	6.6L TD	10,000b
Express/ Savana 3500 SWB CV 2WD	4.8L V-8	6,200b
Express/ Savana 3500 SWB CV 2WD	4.8L V-8	7,200c
Express/ Savana 3500 SWB CV 2WD	6.0L V-8	8,200b
Express/ Savana 3500 SWB CV 2WD	6.0L V-8	10,000c
Express/ Savana 3500 SWB CV 2WD	6.6L TD	10,000b
Express/ Savana 3500 LWB CV 2WD	4.8L V-8	6,000b
Express/ Savana 3500 LWB CV 2WD	4.8L V-8	7,000c
Express/ Savana 3500 LWB CV 2WD	6.0L V-8	8,000b
Express/ Savana 3500 LWB CV 2WD	6.0L V-8	10,000c
Express/ Savana 3500 LWB CV 2WD	6.6L TD	10,000b
Express/ Savana 3500 SWB PV 2WD	6.0L V-8	7,700b
Express/ Savana 3500 SWB PV 2WD	6.0L V-8	9,700c
Express/ Savana 3500 SWB PV 2WD	6.6L TD	10,000c
Express/ Savana 3500 LWB PV 2WD	6.0L V-8	7,400b

Express/ Savana 3500 LWB PV 2WD	6.0L V-8	9,400c
Express/ Savana 3500 LWB PV 2WD	6.6L TD	10,000b

a=3.42:1 axle ratio; b= 3.73:1 axle ratio; c=4.10:1 axle ratio. **Note:** Availability of certain engine/chassis combinations varies between Chevrolet/GMC models. See your dealer for details.

## Chevrolet Avalanche

Vehicle	Engine	Tow Limit (Lb)
Avalanche 1500 2WD	5.3L V-8	7,300b
Avalanche 1500 2WD	5.3L V-8	8,200d
Avalanche 1500 4WD	5.3L V-8	7,100b
Avalanche 1500 4WD	5.3L V-8	7,900d
Avalanche 2500 4WD	8.1L V-8	10,200c
Avalanche 2500 4WD	8.1L V-8	12,000d

b=3.42:1 axle ratio; c=3.73:1 axle ratio; d=4.10:1 axle ratio.

## Chevrolet Silverado/GMC Sierra, Light Duty, Automatic Transmission, Conventional/Fifth-Wheel Towing

Vehicle	Engine	Tow Limit (Lb) Conv./Fifth-Wheel
1500 Reg Cab SWB 2WD	4.3L V-6	5,000b
1500 Reg Cab SWB 2WD	4.8L V-8	6,400b
1500 Reg Cab SWB 2WD	4.8L V-8	7,400d
1500 Reg Cab SWB 2WD	5.3L V-8	7,400b
1500 Reg Cab SWB 2WD	5.3L V-8	8,400d
1500 Reg Cab SWB 4WD	4.3L V-6	5,100d/NA
1500 Reg Cab SWB 4WD	4.8L V-8	7,100c/d
1500 Reg Cab SWB 4WD	4.8L V-8	8,100e/7,300e
1500 Reg Cab SWB 4WD	5.3L V-8	8,100c/d/7,300c/d/e
1500 Reg Cab SWB 4WD	5.3L V-8	9,100e/7,300e
1500 Reg Cab LWB 2WD	4.3L V-6	4,800b/NA
1500 Reg Cab LWB 2WD	4.8L V-8	6,200b
1500 Reg Cab LWB 2WD	4.8L V-8	7,200d
1500 Reg Cab LWB 2WD	5.3L V-8	7,200b
1500 Reg Cab LWB 2WD	5.3L V-8	8,200d
1500 Reg Cab LWB 4WD	4.3L V-6	5,000c/d/NA
1500 Reg Cab LWB 4WD	4.8L V-8	6,900c/6,900c/d
1500 Reg Cab LWB 4WD	4.8L V-8	7,900e
1500 Reg Cab LWB 4WD	5.3L V-8	7,900c/d
1500 Reg Cab LWB 4WD	5.3L V-8	8,900e/8,300e
1500 Ext Cab SWB 2WD (1)	5.3L V-8	7,000b/NA
1500 Ext Cab SWB 2WD (1)	5.3L V-8	8,000d/NA
1500 Ext Cab SWB 4WD (1)	5.3L V-8	7,700c/d/NA

# 2006 Towing Guide

1500 Ext Cab SWB 4WD (1)	5.3L V-8	8,700e/NA
1500 Ext Cab SWB 2WD (2)	4.3L V-6	4,600b/NA
1500 Ext Cab SWB 2WD (2)	4.3L V-6	5,100d/NA
1500 Ext Cab SWB 2WD (2)	4.8L V-8	5,900b
1500 Ext Cab SWB 2WD (2)	4.8L V-8	6,900d/6,800d
1500 Ext Cab SWB 2WD (2)	5.3L V-8	6,900b/6,800b
1500 Ext Cab SWB 2WD (2)	5.3L V-8	7,900d/6,800d
1500 Ext Cab SWB 2WD (2)	6.0L V-8	10,400d/6,900d
1500 Ext Cab SWB 2WD (2) (4)	6.0L V-8	7,800d
1500 Ext Cab SWB 4WD (2)	4.8L V-8	6,700c/d
1500 Ext Cab SWB 4WD (2)	4.8L V-8	7,700e/6,900e
1500 Ext Cab SWB 4WD (2) (3)	5.3L V-8	7,700c/d/ 6,900c/d
1500 Ext Cab SWB 4WD (2) (3)	5.3L V-8	8,700e/6,900e
1500 Ext Cab SWB 4WD (2)	6.0L V-8	10,000e/NA
1500 CC SWB 2WD (1)	5.3L V-8	6,700b/NA
1500 CC SWB 2WD (1)	5.3L V-8	7,700d/NA
1500 CC SWB 2WD (1)	6.0L V-8	10,100
1500 CC SWB 4WD (1)	5.3L V-8	7,400c/d/ NA
1500 CC SWB 4WD (1)	5.3L V-8	8,400e/NA
1500 CC SWB 4WD (1)	6.0L V-8	9,900e
1500 CC SWB 4WD Denali(1)	6.0L V-8	8,100e
1500 CC SWB 2WD (2)	6.0L V-8	8,300d
1500 CC SWB 2WD (2)	6.0L V-8	10,300e
1500 CC SWB 4WD (2)	6.0L V-8	7,900d
1500 CC SWB 4WD (2)	6.0L V-8	9,900e
1500 Ext Cab LWB 2WD	4.8L V-8	5,800b
1500 Ext Cab LWB 2WD	4.8L V-8	6,800d
1500 Ext Cab LWB 2WD	5.3L V-8	6,800b
1500 Ext Cab LWB 2WD	5.3L V-8	7,800d/7,600d
1500 Ext Cab LWB 4WD	4.8L V-8	6,500c/d
1500 Ext Cab LWB 4WD	4.8L V-8	7,500e
1500 Ext Cab LWB 4WD	5.3L V-8	7,500c/d
1500 Ext Cab LWB 4WD	5.3L V-8	8,500e

## Chevrolet Silverado/GMC Sierra, Light-Duty, Manual Transmission, Conventional/Fifth-Wheel Towing

Vehicle	Engine	Tow Limit (Lb) Conv./Fifth-Wheel
1500 Reg Cab SWB 2WD	4.3L V-6	4,000b
1500 Reg Cab SWB 2WD	4.8L V-8	4,400b
1500 Reg Cab SWB 2WD	4.8L V-8	5,400d
1500 Reg Cab SWB 4WD	4.3L V-6	4,100d
1500 Reg Cab SWB 4WD	4.8L V-8	5,100c/d
1500 Reg Cab SWB 4WD	4.8L V-8	6,100e
1500 Reg Cab LWB 2WD	4.3L V-6	3,800b
1500 Reg Cab LWB 2WD	4.8L V-8	4,200b
1500 Reg Cab LWB 2WD	4.8L V-8	5,200d
1500 Reg Cab LWB 4WD	4.3L V-6	4,000d

1500 Reg Cab LWB 4WD	4.8L V-8	4,900c/d
1500 Reg Cab LWB 4WD	4.8L V-8	5,900e
1500 Ext Cab SWB 2WD	4.3L V-6	3,600b
1500 Ext Cab SWB 2WD	4.8L V-8	3,900b
1500 Ext Cab SWB 2WD	4.8L V-8	4,900d
1500 Ext Cab SWB 4WD	4.8L V-8	4,700c/d
1500 Ext Cab SWB 4WD	4.8L V-8	5,700e
1500 Ext Cab LWB 2WD	4.8L V-8	3,800b
1500 Ext Cab LWB 2WD	4.8L V-8	4,800d
1500 Ext Cab LWB 4WD	4.8L V-8	4,500c/d
1500 Ext Cab LWB 4WD	4.8L V-8	5,500e

## Chevrolet Silverado/GMC Sierra, Heavy-Duty, Automatic or Manual Transmission, Conventional/Fifth-Wheel Towing

Vehicle	Engine	Tow Limit (Lb) Conv./Fifth-Wheel
2500 Reg Cab LWB 2WD	6.0L V-8	10,500e
2500 Reg Cab LWB 2WD	8.1L V-8	12,000d/e/ 14,100d, 16,100e
2500 Reg Cab LWB 2WD	6.6L TD	12,000e/15,900e
2500 Reg Cab LWB 4WD	6.0L V-8	10,300e
2500 Reg Cab LWB 4WD	8.1L V-8	12,000d/e/ 13,800d, 15,800e
2500 Reg Cab LWB 4WD	6.6L TD	12,000d/15,600d
2500 Ext Cab SWB 2WD	6.0L V-8	10,300e
2500 Ext Cab SWB 2WD	8.1L V-8	12,000d/e/ 13,900d, 15,900e
2500 Ext Cab SWB 2WD	6.6L TD	12,000d/15,700d
2500 Ext Cab SWB 4WD	6.0L V-8	10,000e
2500 Ext Cab SWB 4WD	8.1L V-8	12,000d/e/ 13,600d, 15,600e
2500 Ext Cab SWB 4WD	6.6L TD	12,000d/15,400d
2500 Ext Cab LWB 2WD	6.0L V-8	10,200e
2500 Ext Cab LWB 2WD	8.1L V-8	12,000d/e/ 13,700d, 15,700e
2500 Ext Cab LWB 2WD	6.6L TD	12,000d/15,500d
2500 Ext Cab LWB 4WD	6.0L V-8	9,900d
2500 Ext Cab LWB 4WD	8.1L V-8	12,000d/e/ 13,400d, 15,400e
2500 Ext Cab LWB 4WD	6.6L TD	12,000d/14,800d
2500 CC SWB 2WD	6.0L V-8	10,100e
2500 CC SWB 2WD	8.1L V-8	12,000d/e/ 13,600d, 15,600e
2500 CC SWB 2WD	6.6L TD	12,000d/15,400d
2500 CC SWB 4WD	6.0L V-8	9,800e
2500 CC SWB 4WD	8.1L V-8	12,000d/e/ 13,300d, 15,300e
2500 CC SWB 4WD	6.6L TD	12,000d/14,200d

2500 CC LWB 2WD	6.0L V-8	10,000e
2500 CC LWB 2WD	8.1L V-8	12,000d/e/ 13,500d, 15,500e
2500 CC LWB 2WD	6.6L TD	12,000d/15,100d
2500 CC LWB 4WD	6.0L V-8	9,700e
2500 CC LWB 4WD	8.1L V-8	12,000d/e/ 13,200d, 14,600e
2500 CC LWB 4WD	6.6L TD	12,000d/13,200d
3500 Reg Cab SRW 2WD	6.0L V-8	10,300e
3500 Reg Cab SRW 4WD	6.0L V-8	10,000e
3500 Reg Cab SRW 4WD	8.1L V-8	12,000e/15,600e
3500 Reg Cab SRW 4WD	6.6L TD	12,000d/15,400d
3500 Reg Cab DRW 4WD	6.0L V-8	9,800e
3500 Reg Cab DRW 4WD	8.1L V-8	12,000e/15,400e
3500 Reg Cab DRW 4WD	6.6L TD	12,000d/15,200d,m
3500 Reg Cab DRW 4WD	6.6L TD	12,000d/16,700d,a
3500 Ext Cab SRW 2WD	6.0L V-8	9,800e
3500 Ext Cab SRW 2WD	8.1L V-8	12,000e/15,500e
3500 Ext Cab SRW 2WD	6.6L TD	12,000d/15,300d
3500 Ext Cab DRW 2WD	6.0L V-8	9,700e
3500 Ext Cab DRW 2WD	8.1L V-8	12,000e/15,300e
3500 Ext Cab DRW 2WD	6.6L TD	12,000d/15,100d,m
3500 Ext Cab DRW 2WD	6.6L TD	12,000d/16,600d,a
3500 ExtCab SRW 4WD	6.0L V-8	9,600e
3500 Ext Cab SRW 4WD	8.1L V-8	12,000e/15,200e
3500 Ext Cab SRW 4WD	6.6L TD	12,000d/15,000d
3500 Ext Cab DRW 4WD	6.0L V-8	9,400e
3500 Ext Cab DRW 4WD	8.1L V-8	12,000e/15,000e
3500 Ext Cab DRW 4WD	6.6L TD	12,000d/14,800d,m
3500 Ext Cab DRW 4WD	6.6L TD	12,000d/16,300d,a
3500 CC SRW 2WD	6.0L V-8	9,600e
3500 CC SRW 2WD	8.1L V-8	12,000e/15,300e
3500 CC SRW 2WD	6.6L TD	12,000d/15,100d
3500 CC DRW 2WD	6.0L V-8	9,500e
3500 CC DRW 2WD	8.1L V-8	12,000e/15,100e
3500 CC DRW 2WD	6.6L TD	12,000d/14,900d,m
3500 CC DRW 2WD	6.6L TD	12,000d/16,400d,a
3500 CC SRW 4WD	6.0L V-8	9,400e
3500 CC SRW 4WD	8.1L V-8	12,000e/15,000e
3500 CC SRW 4WD	6.6L TD	12,000d/14,700d
3500 CC DRW 4WD	6.0L V-8	9,200e
3500 CC DRW 4WD	8.1L V-8	12,000e/14,800e
3500 CC DRW 4WD	6.6L TD	12,000d/14,500d,m
3500 CC DRW 4WD	6.6L TD	12,000d/16,000d,a

**a**=automatic transmission; **b**=3.23:1 axle ratio; **c**=3.42:1 axle ratio; **d**=3.73:1 axle ratio; **e**=4.10:1 axle ratio; **m**=manual transmission; **(1)**=With 68-inch box; **(2)**=With 78-inch box; **(3)**=Deduct 200 lb for Parallel Hybrid models; **(4)**=Silverado SS package; **CC**=Crew Cab.

## Chevrolet Tahoe and Suburban, GMC Yukon, Yukon XL, Yukon Denali and Yukon XL Denali, 1500 Series

Vehicle	Engine	Tow Limit (Lb)
Tahoe/Yukon 2WD	4.8L V-8	5,700a
Tahoe/Yukon 2WD	4.8L V-8	6,700c
Tahoe/Yukon 2WD	5.3L V-8	6,700a
Tahoe/Yukon 2WD	5.3L V-8	7,700c
Tahoe/Yukon 2WD SP	4.8L V-8	5,600a
Tahoe/Yukon 2WD SP	4.8L V-8	6,600c
Tahoe/Yukon 2WD SP	5.3L V-8	6,600a
Tahoe/Yukon 2WD SP	5.3L V-8	7,600c
Tahoe/Yukon 4WD	4.8L V-8	6,500b
Tahoe/Yukon 4WD	4.8L V-8	7,500d
Tahoe/Yukon 4WD	5.3L V-8	7,500b
Tahoe/Yukon 4WD	5.3L V-8	7,700d
Yukon Denali AWD	6.0L V-8	8,100c
Tahoe/Yukon 4WD SP	4.8L V-8	6,300b
Tahoe/Yukon 4WD SP	4.8L V-8	7,300d
Tahoe/Yukon 4WD SP	5.3L V-8	7,300b
Tahoe/Yukon 4WD SP	5.3L V-8	8,300d
Tahoe/Yukon 4WD TRS	4.8L V-8	6,400b
Tahoe/Yukon 4WD TRS	4.8L V-8	7,400d
Tahoe/Yukon 4WD TRS	5.3L V-8	7,400b
Tahoe/Yukon 4WD TRS	5.3L V-8	8,400d
Suburban/Yukon XL 2WD	5.3L V-8	7,500b
Suburban/Yukon XL 2WD	5.3L V-8	8,500d
Suburban/Yukon XL 2WD SP	5.3L V-8	7,200b
Suburban/Yukon XL 2WD SP	5.3L V-8	8,200d
Suburban/Yukon XL 4WD	5.3L V-8	7,200b
Suburban/Yukon XL 4WD	5.3L V-8	8,200d
Yukon XL Denali AWD	6.0L V-8	7,900c
Suburban/Yukon XL 4WD SP	5.3L V-8	7,000b
Suburban/Yukon XL 4WD SP	5.3L V-8	7,600d
Suburban 4WD PP	5.3L V-8	8,000d

**a**=3.23:1 axle ratio; **b**=3.42:1 axle ratio; **c**=3.73:1 axle ratio; **d**=4.10:1 axle ratio; **SP**=Sport Package; **TRS**=Third-Row-Seat model; **PP**=With Suburban Performance Package.

## Chevrolet Suburban, GMC Yukon XL, 2500 Series

Vehicle	Engine	Tow Limit (Lb)
Suburban/Yukon XL 2WD	6.0L V-8	7,900c
Suburban/Yukon XL 2WD	6.0L V-8	9,900d
Suburban/Yukon XL 2WD	8.1L V-8	10,600c
Suburban/Yukon XL 2WD	8.1L V-8	12,000d
Suburban/Yukon XL 4WD	6.0L V-8	7,600c
Suburban/Yukon XL 4WD	6.0L V-8	9,600d
Suburban/Yukon XL 4WD	8.1L V-8	10,300c

# 2006 Towing Guide

Suburban/Yukon XL 4WD	8.1L V-8	12,000d
-----------------------	----------	---------

**c**=3.73:1 axle ratio; **d**=4.10:1 axle ratio.

## Chevrolet TrailBlazer/ GMC Envoy

Vehicle	Engine	Tow Limit (Lb)
TrailBlazer/ Envoy SWB 2WD	4.2L I-6	5,400b/5,300b
TrailBlazer/ Envoy SWB 2WD	4.2L I-6	5,900c/5,800c
TrailBlazer/ Envoy SWB 2WD	4.2L I-6	6,400d/6,300d
TrailBlazer/ Envoy SWB 2WD	5.3L V-8	6,300b/6,100b
TrailBlazer/ Envoy SWB 2WD	5.3L V-8	6,800b/6,600b
TrailBlazer/ Envoy SWB 4WD	4.2L I-6	5,200b
TrailBlazer/ Envoy SWB 4WD	4.2L I-6	5,700c
TrailBlazer/ Envoy SWB 4WD	4.2L I-6	6,200d
TrailBlazer/ Envoy SWB 4WD	5.3L V-8	6,100b/6,000b
TrailBlazer/ Envoy SWB 4WD	5.3L V-8	6,600c/6,500c
TrailBlazer/ Envoy LWB 2WD	4.2L I-6	5,000b
TrailBlazer/ Envoy LWB 2WD	4.2L I-6	5,500c
TrailBlazer/ Envoy LWB 2WD	4.2L I-6	6,000d
TrailBlazer/ Envoy LWB 2WD	5.3L V-8	5,900b/5,700b
TrailBlazer/ Envoy LWB 2WD	5.3L V-8	6,800c/6,200b
TrailBlazer/ Envoy LWB 4WD	4.2L I-6	4,800b
TrailBlazer/ Envoy LWB 4WD	4.2L I-6	5,300c
TrailBlazer/ Envoy LWB 4WD	4.2L I-6	5,800d
TrailBlazer/ Envoy LWB 4WD	5.3L V-8	5,700b/5,600b
TrailBlazer/ Envoy LWB 4WD	5.3L V-8	6,500c/6,000c
TrailBlazer SS 2WD	6.0L V-8	6,700
TrailBlazer SS 4WD	6.0L V-8	6,500

**b**=3.42:1 axle ratio; **c**=3.73:1 axle ratio; **d**=4.10:1 axle ratio.

## DaimlerChrysler Chrysler Town and Country, Dodge Caravan/Grand Caravan

Vehicle	Engine	Tow Limit (Lb)
T&C, Caravan/Grand Caravan	3.3L V-6	2,000
T&C, Caravan/Grand Caravan	3.3L V-6	3,600t
T&C, Caravan/Grand Caravan	3.8L V-6	2,000
T&C, Caravan/Grand Caravan	3.8L V-6	3,800t

## Dakota

Vehicle	Engine	Tow Limit (Lb)
Dakota CC 2WD	3.7L V-6	3,300m,b
Dakota CC 2WD	3.7L V-6	4,100m,c
Dakota CC 2WD	3.7L V-6	4,600a4,c
Dakota CC 2WD	3.7L V-6	4,900a4,d
Dakota CC 2WD	4.7L V-8	5,000m,b
Dakota CC 2WD	4.7L V-8	5,500m,c
Dakota CC 2WD	4.7L V-8	5,950a5,c
Dakota CC 2WD	4.7L V-8	7,150a5,d

Dakota CC 4WD	3.7L V-6	3,900m,c
Dakota CC 4WD	3.7L V-6	4,400a4,c
Dakota CC 4WD	3.7L V-6	4,700a4,d
Dakota CC 4WD	4.7L V-8	5,350m,c
Dakota CC 4WD	4.7L V-8	5,800a5,c
Dakota CC 4WD	4.7L V-8	7,000a5,d
Dakota QC 2WD	3.7L V-6	3,150m,b
Dakota QC 2WD	3.7L V-6	3,950m,c
Dakota QC 2WD	3.7L V-6	4,500a4,c
Dakota QC 2WD	3.7L V-6	4,800a4,d
Dakota QC 2WD	4.7L V-8	4,900m,b
Dakota QC 2WD	4.7L V-8	5,400m,c
Dakota QC 2WD	4.7L V-8	5,850a5,c
Dakota QC 2WD	4.7L V-8	7,050a5,d
Dakota QC 4WD	3.7L V-6	3,800m,c
Dakota QC 4WD	3.7L V-6	4,300a4,c
Dakota QC 4WD	3.7L V-6	4,600a4,d
Dakota QC 4WD	4.7L V-8	5,250m,c
Dakota QC 4WD	4.7L V-8	5,650a5,c
Dakota QC 4WD	4.7L V-8	6,850a5,d

**b**=3.21:1 axle ratio; **c**=3.55:1 axle ratio; **d**=3.92:1 axle ratio; **m**=manual transmission; **CC**=Club Cab; **QC**=Quad Cab. **NOTE**: Actual towing capacity may vary (usually by 100 lb or less, depending on equipment, trim level).

## Durango

Vehicle	Engine	Tow Limit (Lb)
Durango 2WD	3.7L V-6	3,750a4,d
Durango 2WD	4.7L V-8	6,000a5,c
Durango 2WD	4.7L V-8	7,400a5,d
Durango 2WD	5.7L V-8	7,350a5,c
Durango 2WD	5.7L V-8	8,950a5,d
Durango 4WD	4.7L V-8	5,850a5,c
Durango 4WD	4.7L V-8	7,200a5,d
Durango 4WD	5.7L V-8	7,150a5,c
Durango 4WD	5.7L V-8	8,650a5,d

**c**=3.55:1 axle ratio; **d**=3.92:1 axle ratio. **NOTE**: Actual towing capacity may vary (usually by 100 lb or less, depending on equipment, trim level).

## Magnum

Vehicle	Engine	Tow Limit (Lb)
Magnum	3.5L V-6	2,000
Magnum	5.7L V-8	2,000
Magnum	5.7L V-8	3,800t

## Ram 1500 Regular and Quad Cab

1500 Reg Cab SB 2WD	3.7L V-6	3,300m,b/c
1500 Reg Cab SB 2WD	3.7L V-6	3,800a,d
1500 Reg Cab SB 2WD	4.7L V-8	4,200m,b
1500 Reg Cab SB 2WD	4.7L V-8	5,700m,d
1500 Reg Cab SB 2WD	4.7L V-8	4,600m,d*

1500 Reg Cab SB 2WD	4.7L V-8	6,650a,c
1500 Reg Cab SB 2WD	4.7L V-8	7,650a,d
1500 Reg Cab SB 2WD	4.7L V-8	6,550a,d*
1500 Reg Cab SB 2WD	5.7L V-8	8,100a,c
1500 Reg Cab SB 2WD	5.7L V-8	9,100a,d
1500 Reg Cab SB 2WD	5.7L V-8	8,000a,d*
1500 Reg Cab SB 4WD	4.7L V-8	4,450m,c
1500 Reg Cab SB 4WD	4.7L V-8	5,450m,d
1500 Reg Cab SB 4WD	4.7L V-8	6,400a,c
1500 Reg Cab SB 4WD	4.7L V-8	7,400a,d
1500 Reg Cab SB 4WD	4.7L V-8	4,350 m,d*
1500 Reg Cab SB 4WD	4.7L V-8	6,300a,d*
1500 Reg Cab SB 4WD	5.7L V-8	7,800a,c
1500 Reg Cab SB 4WD	5.7L V-8	7,800a,d*
1500 Reg Cab SB 4WD	5.7L V-8	8,800a,d*
1500 Reg Cab LB 2WD	3.7L V-6	3,050m,b/c
1500 Reg Cab LB 2WD	3.7L V-6	3,550a,d
1500 Reg Cab LB 2WD	4.7L V-8	4,000m,b
1500 Reg Cab LB 2WD	4.7L V-8	5,500m,d
1500 Reg Cab LB 2WD	4.7L V-8	6,450a,c
1500 Reg Cab LB 2WD	4.7L V-8	7,450a,d
1500 Reg Cab LB 2WD	5.7L V-8	7,900a,c
1500 Reg Cab LB 2WD	5.7L V-8	8,900a,d
1500 Reg Cab LB 4WD	4.7L V-8	4,250m,c
1500 Reg Cab LB 4WD	4.7L V-8	5,250m,d
1500 Reg Cab LB 4WD	4.7L V-8	6,200a,c
1500 Reg Cab LB 4WD	4.7L V-8	7,200a,d
1500 Reg Cab LB 4WD	5.7L V-8	7,600a,c
1500 Reg Cab LB 4WD	5.7L V-8	8,600a,d
1500 QC SB 2WD	3.7L V-6	2,900m,b/c
1500 QC SB 2WD	3.7L V-6	3,400m,d
1500 QC SB 2WD	4.7L V-8	3,850m,b
1500 QC SB 2WD	4.7L V-8	5,350m,d
1500 QC SB 2WD	4.7L V-8	6,300a,c
1500 QC SB 2WD	4.7L V-8	7,300a,d
1500 QC SB 2WD	4.7L V-8	4,300m,d*
1500 QC SB 2WD	4.7L V-8	6,200a,d
1500 QC SB 2WD	5.7L V-8	7,700a,c
1500 QC SB 2WD	5.7L V-8	8,700a,d
1500 QC SB 2WD	5.7L V-8	7,650a,d*
1500 QC SB 4WD	4.7L V-8	4,100m,c
1500 QC SB 4WD	4.7L V-8	5,100m,d
1500 QC SB 4WD	4.7L V-8	6,050a,c
1500 QC SB 4WD	4.7L V-8	7,050a,d
1500 QC SB 4WD	4.7L V-8	4,050m,d*
1500 QC SB 4WD	4.7L V-8	6,000a,d*
1500 QC SB 4WD	5.7L V-8	7,500a,c
1500 QC SB 4WD	5.7L V-8	7,400a,d*
1500 QC SB 4WD	5.7L V-8	8,500a,d

1500 QC LB 2WD	4.7L V-8	3,700m,a
1500 QC LB 2WD	4.7L V-8	5,200m,d
1500 QC LB 2WD	4.7L V-8	6,100a,c
1500 QC LB 2WD	4.7L V-8	7,100a,d
1500 QC LB 2WD	5.7L V-8	7,550a,c
1500 QC LB 2WD	5.7L V-8	8,550a,d
1500 QC LB 4WD	4.7L V-8	4,950m,d
1500 QC LB 4WD	4.7L V-8	6,900a,d
1500 QC LB 4WD	5.7L V-8	8,250a,d

a=automatic; b=3.21:1 axle ratio; c=3.55:1 axle ratio; d=3.92:1 axle ratio;  
m=manual transmission; \*Equipped with 20-inch wheels; QC=Quad Cab.

Note: Actual towing capacity may vary (usually by 100 lb or less, depending on equipment, trim level)

### Ram 2500/3500, Regular and Quad Cab

Vehicle	Engine	Tow Limit (LB)
2500 Reg Cab LB 2WD	5.7L V-8	9,400m,b
2500 Reg Cab LB 2WD	5.7L V-8	11,400m,c
2500 Reg Cab LB 2WD	5.7L V-8	9,450a,b
2500 Reg Cab LB 2WD	5.7L V-8	11,450a,c
2500 Reg Cab LB 2WD	5.9L TD	13,550m,b
2500 Reg Cab LB 2WD	5.9L TD	13,650a,b/c
2500 Reg Cab LB 4WD	5.7L V-8	8,950m,b
2500 Reg Cab LB 4WD	5.7L V-8	10,950m,c
2500 Reg Cab LB 4WD	5.7L V-8	9,000a,b
2500 Reg Cab LB 4WD	5.7L V-8	11,000a,c
2500 Reg Cab LB 4WD	5.9L TD	13,200m,b
2500 Reg Cab LB 4WD	5.9L TD	13,250a,b/c
2500 QC SB 2WD	5.7L V-8	9,200m,b
2500 QC SB 2WD	5.7L V-8	11,200m,c
2500 QC SB 2WD	5.7L V-8	9,250a,b
2500 QC SB 2WD	5.7L V-8	11,250a,c
2500 QC SB 2WD	5.9L TD	13,400m,b
2500 QC SB 2WD	5.9L TD	13,500a,b/c
2500 QC SB 4WD	5.7L V-8	8,800m,b
2500 QC SB 4WD	5.7L V-8	10,800m,c
2500 QC SB 4WD	5.7L V-8	8,850a,b
2500 QC SB 4WD	5.7L V-8	10,850a,c
2500 QC SB PW 4WD	5.7L V-8	10,500m,d
2500 QC SB PW 4WD	5.7L V-8	10,550a,d
2500 QC SB 4WD	5.9L TD	13,000m,b
2500 QC SB 4WD	5.9L TD	13,100a,b/c
2500 QC LB 2WD	5.7L V-8	9,100m,b
2500 QC LB 2WD	5.7L V-8	11,100m,c
2500 QC LB 2WD	5.7L V-8	9,150a,b
2500 QC LB 2WD	5.7L V-8	11,150a,c
2500 QC LB 2WD	5.9L TD	13,250m,b
2500 QC LB 2WD	5.9L TD	13,350a,b/c
2500 QC LB 4WD	5.7L V-8	8,650m,b
2500 QC LB 4WD	5.7L V-8	10,650m,c

# 2006 Towing Guide

2500 QC LB 4WD	5.7L V-8	8,700a,b
2500 QC LB 4WD	5.7L V-8	10,700a,c
2500 QC LB 4WD	5.9L TD	12,850m,b
2500 QC LB 4WD	5.9L TD	12,900a,b/c
3500 Reg Cab LB DRW 2WD	5.7L V-8	10,900m,c
3500 Reg Cab LB DRW 2WD	5.7L V-8	10,950a,c
3500 Reg Cab LB DRW 2WD	5.9L TD	16,150m,b
3500 Reg Cab LB DRW 2WD	5.9L TD	14,200a,b
3500 Reg Cab LB DRW 2WD	5.9L TD	16,200a,d
3500 Reg Cab LB DRW 4WD	5.7L V-8	10,500m,c
3500 Reg Cab LB DRW 4WD	5.7L V-8	10,550a,c
3500 Reg Cab LB DRW 4WD	5.9L TD	15,900m,b
3500 Reg Cab LB DRW 4WD	5.9L TD	13,950a,b
3500 Reg Cab LB DRW 4WD	5.9L TD	15,950a,c
3500 QC SB SRW 2WD	5.9L TD	16,350m,b
3500 QC SB SRW 2WD	5.9L TD	14,400a,b
3500 QC SB SRW 2WD	5.9L TD	16,400a,c
3500 QC SB SRW 4WD	5.9L TD	15,900m,b
3500 QC SB SRW 4WD	5.9L TD	14,000a,b
3500 QC SB SRW 4WD	5.9L TD	16,000a,c
3500 QC LB SRW 2WD	5.9L TD	16,200m,b
3500 QC LB SRW 2WD	5.9L TD	14,300a,b
3500 QC LB SRW 2WD	5.9L TD	16,300a,c
3500 QC LB SRW 4WD	5.9L TD	15,750m,b
3500 QC LB SRW 4WD	5.9L TD	13,850a,b
3500 QC LB SRW 4WD	5.9L TD	15,850a,c
3500 QC LB DRW 2WD	5.7L V-8	10,650m,c
3500 QC LB DRW 2WD	5.7L V-8	10,700a,c
3500 QC LB DRW 2WD	5.9L TD	15,850m,b
3500 QC LB DRW 2WD	5.9L TD	13,900a,b
3500 QC LB DRW 2WD	5.9L TD	15,900a,c
3500 QC LB DRW 4WD	5.7L V-8	10,200m,c
3500 QC LB DRW 4WD	5.7L V-8	10,250a,c
3500 QC LB DRW 4WD	5.9L TD	15,400m,b
3500 QC LB DRW 4WD	5.9L TD	13,500a,b
3500 QC LB DRW 4WD	5.9L TD	15,500a,c

a=automatic transmission; b=3.73:1 axle ratio; c=4.10:1 axle ratio; d=4.56:1 axle ratio; m=manual transmission; LB=Long Bed; SB=Short Bed; PW=Power Wagon; QC=Quad Cab; Note: Actual towing capacity may vary (usually by 150 lb or less, depending on equipment, trim level).

## Ram 1500/2500/3500 Mega Cab

Vehicle	Engine	Tow Limit (LB)
1500 2WD	5.7L V-8	6,750a,b
1500 2WD	5.7L V-8	7,750a,c
1500 4WD	5.7L V-8	6,350a,b
1500 4WD	5.7L V-8	7,350a,c
2500 2WD	5.7L V-8	8,650a,b
2500 2WD	5.7L V-8	10,650a,c
2500 2WD	5.9L TD	12,900m/a,b/c

2500 4WD	5.7L V-8	8,150a,b
2500 4WD	5.7L V-8	10,150a,c
2500 4WD	5.9L TD	12,400m/a,b/c
3500 2WD	5.9L TD	15,800m,b
3500 2WD	5.9L TD	13,800a,b
3500 2WD	5.9L TD	15,800a,c
3500 4WD	5.9L TD	15,350m,b
3500 4WD	5.9L TD	13,300a,b
3500 4WD	5.9L TD	15,300a,c

a=automatic transmission; b=3.73:1 axle ratio; c=4.10:1 axle ratio; m=manual transmission. Note: Actual towing capacity may vary (usually by 150 lb or less, depending on equipment, trim level).

## Sprinter

Vehicle	Engine	Tow Limit (LB)
Sprinter	2.7L TD	5,000

## Ford E-Series

Vehicle	Engine	Van/Wagon Tow Limit (LB)
E-150	4.6L V-8	6,500b/6,100b
E-150	5.4L V-8	6,900b/6,500b
E-250	4.6L V-8	6,100c/NA
E-250	4.6L V-8	6,600d/NA
E-250	5.4L V-8	7,500d/NA
E-250 Ext	4.6L V-8	6,000d/NA
E-250 Ext	4.6L V-8	6,400d/NA
E-250 Ext	5.4L V-8	7,300c/NA
E-350	5.4L V-8	6,300b/7,000c
E-350	5.4L V-8	7,300c/d/7,000
E-350	6.8L V-10	9,200c/8,800c
E-350	6.8L V-10	10,000d
E-350	6.0L TD	9,700b/9,300b
E-350	6.0L TD	10,000d
E-350 Ext	5.4L V-8	7,200c/6,700c
E-350 Ext	6.8L V-10	9,000c/NA
E-350 Ext	6.8L V-10	10,000d/NA
E-350 Ext	6.0L TD	9,500b/NA
E-350 Ext	6.0L TD	10,000d/NA

Note: For maximum trailer weights with Crew Van, deduct 300 lb with E-150/250 Regular Van or 200 lb with E-350 Super Duty from weights in chart (except with 18,500- and 20,000-lb ecmw).

## Ranger, Automatic Transmission

Vehicle	Engine	Tow Limit (LB)
Reg Cab Short Box, 2WD	2.3 I-4	2,260d
Reg Cab Short Box, 2WD	3.0L V-6	2,620c
Reg Cab Short Box, 2WD	3.0L V-6	2,460d (1)
Reg Cab Long Box, 2WD	3.0L V-6	2,560c

Reg Cab Long Box, 2WD	4.0L V-6	6,000b
Reg Cab Short Box, 4WD	3.0L V-6	2,320d
Reg Cab Long Box, 4WD	4.0L V-6	5,680d
SC Short Box, 2WD	3.0L V-6	2,440c
SC Short Box, 2WD	3.0L V-6	2,300d (1)
SC Short Box, 2WD	4.0L V-6	5,860b
SC Short Box, 2WD	4.0L V-6	5,720b (1)
SC Short Box, 4WD	4.0L V-6	5,580d (2)

### Ranger, Manual Transmission

Vehicle	Engine	Tow Limit (LB)
Reg Cab Short Box, 2WD	3.0L V-6	2,660c
Reg Cab Short Box, 2WD	3.0L V-6	2,500 (1)
Reg Cab Short Box, 4WD	3.0L V-6	2,340d
Reg Cab Long Box, 4WD	4.0L V-6	3,220d
SC Short Box, 2WD	3.0L V-6	2,480c
SC Short Box, 2WD	3.0L V-6	2340d (1)
SC Short Box, 2WD	4.0L V-6	3,400b
SC Short Box, 2WD	4.0L V-6	3,280b (1)
SC Short Box, 4WD	4.0L V-6	3,120 (3)

Short Box=6 feet; Long Box=7 feet; (1): Ranger Edge only; (2): 5,300 lb with FX4 Level II package; (3): 2,840 lb with FX4 Level II package.

### Escape, Explorer, Expedition

Vehicle	Engine	Tow Limit (LB)
Escape	3.0L V-6	3,500t
Explorer 2WD, five pass.	4.0L V-6	5,390
Explorer 2WD, six pass.	4.0L V-6	5,320
Explorer 2WD, seven pass.	4.0L V-6	5,320
Explorer 2WD, five pass.	4.6L V-8	7,300
Explorer 2WD, six pass.	4.6L V-8	7,230
Explorer 2WD, seven pass.	4.6L V-8	7,230
Explorer 4WD, five pass.	4.0L V-6	5,210
Explorer 4WD, six pass.	4.0L V-6	5,140
Explorer 4WD, seven pass.	4.0L V-6	5,140
Explorer 4WD, five pass.	4.6L V-8	7,120
Explorer 4WD, six pass.	4.6L V-8	7,050
Explorer 4WD, seven pass.	4.6L V-8	7,050
Expedition 2WD	5.4L V-8	6,000a
Expedition 2WD	5.4L V-8	8,900c
Expedition 4WD	5.4L V-8	6,000c
Expedition 4WD	5.4L V-8	8,600c,t

### Explorer Sport Trac

Vehicle	Engine	Tow Limit (LB)
Sport Trac 2WD	4.0L V-6	5,300
Sport Trac 4WD	4.0L V-6	5,080

### Ford F-150 Regular Cab/SuperCrew Conventional Towing, Automatic Transmission

Vehicle	Engine	Tow Limit (LB)
Reg Cab SWB 2WD	4.2L V-6	5,200b
Reg Cab SWB 2WD	4.2L V-6	5,700c
Reg Cab SWB 2WD	4.6L V-8	6,600b
Reg Cab SWB 2WD	4.6L V-8	7,100c
Reg Cab SWB 2WD	5.4L V-8	8,000b
Reg Cab SWB 2WD	5.4L V-8	8,500c
Reg Cab LWB 2WD	4.2L V-6	5,100b
Reg Cab LWB 2WD	4.2L V-6	5,600c
Reg Cab LWB 2WD	4.6L V-8	6,700b
Reg Cab LWB 2WD	4.6L V-8	7,200c
Reg Cab LWB 2WD	5.4L V-8	8,800b
Reg Cab LWB 2WD	5.4L V-8	9,800c
Reg Cab LWB 2WD	5.4L V-8	9,900d
Reg Cab SWB 4WD	4.6L V-8	6,300b
Reg Cab SWB 4WD	4.6L V-8	6,800c
Reg Cab SWB 4WD	5.4L V-8	7,700b
Reg Cab SWB 4WD	5.4L V-8	8,200c
Reg Cab LWB 4WD	4.6L V-8	6,400b
Reg Cab LWB 4WD	4.6L V-8	6,900c
Reg Cab LWB 4WD	5.4L V-8	8,500b
Reg Cab LWB 4WD	5.4L V-8	9,500c/d
SuperCrew SWB 2WD	4.6L V-8	6,300b
SuperCrew SWB 2WD	4.6L V-8	6,800c
SuperCrew SWB 2WD	5.4L V-8	8,500b
SuperCrew SWB 2WD	5.4L V-8	9,500c
SuperCrew LWB 2WD	4.6L V-8	6,200b
SuperCrew LWB 2WD	4.6L V-8	6,700c
SuperCrew LWB 2WD	5.4L V-8	8,400b
SuperCrew LWB 2WD	5.4L V-8	9,400c
SuperCrew SWB 4WD	4.6L V-8	6,500c
SuperCrew SWB 4WD	5.4L V-8	8,200b
SuperCrew SWB 4WD	5.4L V-8	9,200c
SuperCrew LWB 4WD	4.6L V-8	6,400b
SuperCrew LWB 4WD	5.4L V-8	8,100b
SuperCrew LWB 4WD	5.4L V-8	9,100c

### Manual Transmission Models

Vehicle	Engine	Tow Limit (LB)
Reg Cab SWB 2WD	4.2L V-6	2,400a
Reg Cab SWB 2WD	4.2L V-6	3,700b
Reg Cab LWB 2WD	4.2L V-6	2,300a
Reg Cab LWB 2WD	4.2L V-6	3,600b

Short Wheelbase=126 inches; Long Wheelbase=144.5 inches; Note: Reduce maximum trailer weight by 500 lb for models with 18 or 20-inch wheels.



# 2006 Towing Guide

## F-150 SuperCab, Conventional Towing, Automatic Transmission

Vehicle	Engine	Tow Limit (Lb)
SC SWB 2WD	4.6L V-8	6,300b
SC SWB 2WD	4.6L V-8	6,800c
SC SWB 2WD	5.4L V-8	7,700b
SC SWB 2WD	5.4L V-8	8,200c
SC LWB 2WD	4.6L V-8	6,400b
SC LWB 2WD	4.6L V-8	6,900c
SC LWB 2WD	5.4L V-8	8,600b
SC LWB 2WD	5.4L V-8	9,500c
SC LWB 2WD H-D	5.4L V-8	5,800c
SC XLWB 2WD	5.4L V-8	9,500d
SC SWB 4WD	4.6L V-8	6,000b
SC SWB 4WD	4.6L V-8	6,500c
SC SWB 4WD	5.4L V-8	7,400b
SC SWB 4WD	5.4L V-8	7,900c
SC LWB 4WD	4.6L V-8	6,200b
SC LWB 4WD	4.6L V-8	6,700c
SC LWB 4WD	5.4L V-8	8,300b
SC LWB 4WD	5.4L V-8	9,300c
SC LWB 4WD H-D	5.4L V-8	5,600c
SC XLWB 4WD	5.4L V-8	9,300d

Short Wheelbase=132.5 inches; Long Wheelbase=144.5 inches; Extra Long Wheelbase=163 inches; **H-D** signifies optional Harley-Davidson Package. **Note:** Reduce maximum trailer weight by 500 Lb for models with 18 or 20-inch wheels.

## F-250/F-350 Super Duty, Conventional Towing, Automatic Transmission

Vehicle	Engine	Tow Limit (Lb)
F-250/350 Reg Cab SRW 2WD	5.4L V-8	10,100c
F-250/350 Reg Cab SRW 2WD	5.4L V-8	12,100d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	12,500d/e
F-250/350 Reg Cab SRW 2WD	6.0L TD	12,500d
F-250/350 SuperCab SRW 2WD	5.4L V-8	9,800c
F-250/350 SuperCab SRW 2WD	5.4L V-8	11,800d
F-250/350 SuperCab SRW 2WD	6.8L V-10	12,500d/e
F-250/350 SuperCab SRW 2WD	6.0L TD	12,500d
F-250/350 Crew Cab SRW 2WD	5.4L V-8	9,500c
F-250/350 Crew Cab SRW 2WD	5.4L V-8	11,600d
F-250/350 Crew Cab SRW 2WD	6.8L V-10	12,500d/e
F-250/350 CC SRW 2WD	6.0L TD	12,500c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	9,700c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	11,700d
F-250/350 Reg Cab SRW 4WD	6.8L V-10	12,500d/e
F-250/350 Reg Cab SRW 4WD	6.0L TD	12,500d
F-250/350 SC SRW 4WD	5.4L V-8	9,300c
F-250/350 SC SRW 4WD	5.4L V-8	11,300d
F-250/350 SC SRW 4WD	6.8L V-10	12,500d/e

F-250/350 SC SRW 4WD	6.0L TD	11,100d
F-250/350 CC SRW 4WD	6.8L V-10	12,500d/e
F-250/350 CC SRW 4WD	6.0L TD	12,500c
F-350 Reg Cab DRW 2WD	5.4L V-8	12,300d
F-350 Reg Cab DRW 2WD	6.8L V-10	15,000d/e
F-350 Reg Cab DRW 2WD	6.0L TD	15,000c
F-350 SC DRW 2WD	5.4L V-8	11,900d
F-350 SC DRW 2WD	6.8L V-10	14,800d
F-350 SC DRW 2WD	6.8L V-10	15,000e
F-350 SC DRW 2WD	6.0L TD	15,000c/d/e
F-350 CC DRW 2WD	6.8L V-10	14,700d
F-350 CC DRW 2WD	6.8L V-10	15,000e
F-350 CC DRW 2WD	6.0L TD	15,000c/d/e
F-350 Reg Cab DRW 4WD	5.4L V-8	11,800d
F-350 Reg Cab DRW 4WD	6.8L V-10	14,700d
F-350 Reg Cab DRW 4WD	6.8L V-10	15,000e
F-350 Reg Cab DRW 4WD	6.0L TD	15,000c/d/e
F-350 SC DRW 4WD	5.4L V-8	11,500d
F-350 SC DRW 4WD	6.8L V-10	14,300d
F-350 SC DRW 4WD	6.8L V-10	15,000e
F-350 SC DRW 4WD	6.0L TD	15,000c/d/e

## F-250/F-350 Super Duty, Conventional Towing, Manual Transmission

Vehicle	Engine	Tow Limit (Lb)
F-250/350 Reg Cab SRW 2WD	5.4L V-8	9,100c
F-250/350 Reg Cab SRW 2WD	5.4L V-8	11,100d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	12,500d/e
F-250/350 Reg Cab SRW 2WD	6.0L TD	12,500c
F-250/350 SC SRW 2WD	5.4L V-8	8,800c
F-250/350 SC SRW 2WD	5.4L V-8	10,800d
F-250/350 SC SRW 2WD	6.8L V-10	12,500d/e
F-250/350 SC SRW 2WD	6.0L TD	12,500c
F-250/350 CC SRW 2WD	5.4L V-8	8,600c
F-250/350 CC SRW 2WD	5.4L V-8	10,600d
F-250/350 CC SRW 2WD	6.8L V-10	12,500d/e
F-250/350 CC SRW 2WD	6.0L TD	12,500c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	8,700c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	10,700d
F-250/350 Reg Cab SRW 4WD	6.8L V-10	12,500d/e
F-250/350 Reg Cab SRW 4WD	6.0L TD	12,000c
F-250/350 SC SRW 4WD	5.4L V-8	8,300c
F-250/350 SC SRW 4WD	5.4L V-8	10,300d
F-250/350 SC SRW 4WD	6.8L V-10	12,500d/e
F-250/350 SC SRW 4WD	6.0L TD	12,500c
F-250/350 CC SRW 4WD	5.4L V-8	8,100c
F-250/350 CC SRW 4WD	5.4L V-8	10,100d
F-250/350 CC SRW 4WD	6.8L V-10	12,500c/d
F-250/350 CC SRW 4WD	6.0L TD	12,500c

F-350 Reg Cab DRW 2WD	5.4L V-8	11,300d
F-350 Reg Cab DRW 2WD	6.8L V-10	14,100d
F-350 Reg Cab DRW 2WD	6.8L V-10	15,000e
F-350 Reg Cab DRW 2WD	6.0L TD	15,000c/d
F-350 SC DRW 2WD	5.4L V-8	10,900d
F-350 SC DRW 2WD	6.8L V-10	13,800d
F-350 SC DRW 2WD	6.8L V-10	15,000e
F-350 SC DRW 2WD	6.0L TD	15,000c/d
F-350 CC DRW 2WD	6.8L V-10	13,600d
F-350 CC DRW 2WD	6.8L V-10	15,000e
F-350 CC DRW 2WD	6.0L TD	15,000c/d
F-350 Reg Cab DRW 4WD	5.4L V-8	10,800d
F-350 Reg Cab DRW 4WD	6.8L V-10	13,700d
F-350 Reg Cab DRW 4WD	6.8L V-10	15,000e
F-350 Reg Cab DRW 4WD	6.0L TD	15,000d/e
F-350 SC DRW 4WD	5.4L V-8	10,500d
F-350 SC DRW 4WD	6.8L V-10	13,300d
F-350 SC DRW 4WD	6.8L V-10	15,000e
F-350 SC DRW 4WD	6.0L TD	15,000c/d
F-350 CC DRW 4WD	6.8L V-10	13,100d
F-350 CC DRW 4WD	6.8L V-10	15,000e
F-350 CC DRW 4WD	6.0L TD	15,000c/d

### F-250/F-350 Super Duty, Fifth-Wheel Towing, Automatic Transmission

Vehicle	Engine	Tow Limit (LB)
F-250/350 Reg Cab SRW 2WD	5.4L V-8	10,100c
F-250/350 Reg Cab SRW 2WD	5.4L V-8	12,100d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	15,000d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	16,500e/17,000e*
F-250/350 Reg Cab SRW 2WD	6.0L TD	16,500c
F-250/350 SC SRW 2WD	5.4L V-8	9,800c
F-250/350 SC SRW 2WD	5.4L V-8	11,800d
F-250/350 SC SRW 2WD	6.8L V-10	14,700d
F-250/350 SC SRW 2WD	6.8L V-10	16,200e/16,700e*
F-250/350 SC SRW 2WD	6.0L TD	16,100c
F-250/350 CC SRW 2WD	5.4L V-8	9,600c
F-250/350 CC SRW 2WD	5.4L V-8	11,600d
F-250/350 CC SRW 2WD	6.8L V-10	14,500d
F-250/350 CC SRW 2WD	6.8L V-10	16,000e/16,500e*
F-250/350 CC SRW 2WD	6.0L TD	15,900c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	9,700c
F-250/350 Reg Cab SRW 4WD	5.4L V-8	11,700d
F-250/350 Reg Cab SRW 4WD	6.8L V-10	14,500d
F-250/350 Reg Cab SRW 4WD	6.8L V-10	16,000e/16,500e*
F-250/350 Reg Cab SRW 4WD	6.0L TD	15,800c
F-250/350 SC SRW 4WD	5.4L V-8	9,300c
F-250/350 SC SRW 4WD	5.4L V-8	11,300d
F-250/350 SC SRW 4WD	6.8L V-10	14,200d

F-250/350 SC SRW 4WD	6.8L V-10	15,700e/16,200e*
F-250/350 SC SRW 4WD	6.0L TD	15,700c
F-250/350 CC SRW 4WD	5.4L V-8	9,100c
F-250/350 CC SRW 4WD	5.4L V-8	11,100d
F-250/350 CC SRW 4WD	6.8L V-10	14,000d
F-250/350 CC SRW 4WD	6.8L V-10	15,500e/16,000e*
F-250/350 CC SRW 4WD	6.0L TD	15,500c
F-350 Reg Cab DRW 2WD	5.4L V-8	12,300d
F-350 Reg Cab DRW 2WD	6.8L V-10	15,200d
F-350 Reg Cab DRW 2WD	6.8L V-10	16,700e
F-350 Reg Cab DRW 2WD	6.0L TD	16,600c/d
F-350 Reg Cab DRW 2WD	6.0L TD	19,200e,t
F-350 SC DRW 2WD	5.4L V-8	11,900d
F-350 SC DRW 2WD	6.8L V-10	14,800d
F-350 SC DRW 2WD	6.8L V-10	16,300e
F-350 SC DRW 2WD	6.0L TD	16,300c/d
F-350 SC DRW 2WD	6.0L TD	18,800e,t
F-350 CC DRW 2WD	6.8L V-10	14,700d
F-350 CC DRW 2WD	6.8L V-10	16,200e
F-350 CC DRW 2WD	6.0L TD	16,100c/d
F-350 CC DRW 2WD	6.0L TD	18,600e,t
F-350 Reg Cab DRW 4WD	5.4L V-8	11,800d
F-350 Reg Cab DRW 4WD	6.8L V-10	14,700d
F-350 Reg Cab DRW 4WD	6.8L V-10	16,200e
F-350 Reg Cab DRW 4WD	6.0L TD	16,200c/d
F-350 Reg Cab DRW 4WD	6.0L TD	18,700e,t
F-350 SC DRW 4WD	5.4L V-8	11,500d
F-350 SC DRW 4WD	6.8L V-10	14,300d
F-350 SC DRW 4WD	6.8L V-10	15,800e
F-350 SC DRW 4WD	6.0L TD	15,800c/d
F-350 SC DRW 4WD	6.0L TD	18,300e,t
F-350 CC DRW 4WD	6.8L V-10	14,200d
F-350 CC DRW 4WD	6.8L V-10	15,700e
F-350 CC DRW 4WD	6.0L TD	15,600c/d
F-350 CC DRW 4WD	6.0L TD	18,100e,t

\*Rating for F-350 SRW only. For F-250/350 SRW models, F-350 weights are shown; F-250 weights are within 100 lb.

### F-250/F-350 Super Duty, Fifth-Wheel Towing, Manual Transmission

Vehicle	Engine	Tow Limit (LB)
F-250/350 Reg Cab SRW 2WD	5.4L V-8	9,100c
F-250/350 Reg Cab SRW 2WD	5.4L V-8	11,100d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	14,000d
F-250/350 Reg Cab SRW 2WD	6.8L V-10	16,000e
F-250/350 Reg Cab SRW 2WD	6.0L TD	16,400c
F-250/350 SC SRW 2WD	5.4L V-8	8,800c
F-250/350 SC SRW 2WD	5.4L V-8	10,800d
F-250/350 SC SRW 2WD	6.8L V-10	13,700d

# 2006 Towing Guide

F-250/350 SC SRW 2WD	6.8L V-10	15,700e
F-250/350 SC SRW 2WD	6.0L TD	16,100c
F-250/350 CC SRW 2WD	5.4L V-8	8,600c
F-250/350 CC SRW 2WD	5.4L V-8	10,600d
F-250/350 CC SRW 2WD	6.8L V-10	13,500d
F-250/350 CC SRW 2WD	6.8L V-10	15,400e
F-250/350 CC SRW 2WD	6.0L TD	15,900c
F-250/F-350 Reg Cab SRW 4WD	5.4L V-8	8,700c
F-250/F-350 Reg Cab SRW 4WD	5.4L V-8	10,700d
F-250/F-350 Reg Cab SRW 4WD	6.8L V-10	13,500d
F-250/F-350 Reg Cab SRW 4WD	6.8L V-10	15,500e
F-250/F-350 Reg Cab SRW 4WD	6.0L TD	16,000c
F-250/F-350 SC SRW 4WD	5.4L V-8	8,300c
F-250/F-350 SC SRW 4WD	5.4L V-8	10,300d
F-250/F-350 SC SRW 4WD	6.8L V-10	13,200d
F-250/F-350 SC SRW 4WD	6.8L V-10	15,200e
F-250/F-350 SC SRW 4WD	6.0L TD	15,600c
F-250/F-350 CC SRW 4WD	5.4L V-8	8,100c
F-250/F-350 CC SRW 4WD	5.4L V-8	10,100d
F-250/F-350 CC SRW 4WD	6.8L V-10	13,000d
F-250/F-350 CC SRW 4WD	6.8L V-10	15,000e
F-250/F-350 CC SRW 4WD	6.0L TD	15,400c
F-350 Reg Cab DRW 2WD	5.4L V-8	11,300d
F-350 Reg Cab DRW 2WD	6.8L V-10	14,100d
F-350 Reg Cab DRW 2WD	6.8L V-10	16,100e
F-350 Reg Cab DRW 2WD	6.0L TD	16,600c/d
F-350 SC DRW 2WD	5.4L V-8	10,900d
F-350 SC DRW 2WD	6.8L V-10	13,800d
F-350 SC DRW 2WD	6.8L V-10	15,800e
F-350 SC DRW 2WD	6.0L TD	16,200c/d
F-350 CC DRW 2WD	6.8L V-10	13,600d
F-350 CC DRW 2WD	6.8L V-10	15,600e
F-350 CC DRW 2WD	6.0L TD	16,100c/d
F-350 Reg Cab DRW 4WD	5.4L V-8	10,800d
F-350 Reg Cab DRW 4WD	6.8L V-10	13,700d
F-350 Reg Cab DRW 4WD	6.8L V-10	15,700e
F-350 Reg Cab DRW 4WD	6.0L TD	16,100c/d
F-350 SC DRW 4WD	5.4L V-8	10,500d
F-350 SC DRW 4WD	6.8L V-10	13,300d
F-350 SC DRW 4WD	6.8L V-10	15,300e
F-350 SC DRW 4WD	6.0L TD	15,800c/d
F-350 CC DRW 4WD	6.8L V-10	13,100d
F-350 CC DRW 4WD	6.8L V-10	15,100e
F-350 CC DRW 4WD	6.0L TD	15,600c/d

## F-450/F-550 Chassis Cab Fifth-Wheel Towing, Automatic Transmission

(Weights below assume 1,000-lb second-unit body weight. Super Duty Chassis cab does not offer a fifth-wheel hitch as a factory-installed option.)

Vehicle	Engine	Tow Limit (Lb)
F-450 RCC DRW 2WD	6.8L V-10	18,400f/g
F-450 RCC DRW 2WD	6.0L TD	18,000e/f
F-450 RCC DRW 2WD	6.0L TD	22,000f,t
F-450 RCC DRW 4WD	6.8L V-10	18,100f/g
F-450 RCC DRW 4WD	6.0L TD	17,700e/f
F-450 RCC DRW 4WD	6.0L TD	21,700f,t
F-550 RCC DRW 2WD	6.8L V-10	18,400f/g
F-550 RCC DRW 2WD	6.0L TD	17,900e/f
F-550 RCC DRW 2WD	6.0L TD	24,900f,t
F-550 RCC DRW 4WD	6.8L V-10	18,000f/g
F-550 RCC DRW 4WD	6.0L TD	17,600e/f
F-550 RCC DRW 4WD	6.0L TD	24,600f,t

**Note:** Weights shown are for 141-inch wheelbase models. For 165-, 189- and 201-inch wheelbase models, weights may be somewhat less (usually 200 pounds less with 165- and 189-inch wheelbase, 400 Lb less with 201-inch wheelbase).

F-450 SCC DRW 2WD	6.8L V-10	18,000f/g
F-450 SCC DRW 2WD	6.0L TD	17,600e/f
F-450 SCC DRW 2WD	6.0L TD	21,600f,t
F-450 SCC DRW 4WD	6.8L V-10	17,700f/g
F-450 SCC DRW 4WD	6.0L TD	17,300e/f
F-450 SCC DRW 4WD	6.0L TD	21,300f,t
F-550 SCC DRW 2WD	6.8L V-10	18,000f/g
F-550 SCC DRW 2WD	6.0L TD	17,600e/f
F-550 SCC DRW 2WD	6.0L TD	24,600f,t
F-550 SCC DRW 4WD	6.8L V-10	17,700f/g
F-550 SCC DRW 4WD	6.0L TD	17,300e/f
F-550 SCC DRW 4WD	6.0L TD	24,300f,t
F-450 CCC DRW 2WD	6.8L V-10	17,800f/g
F-450 CCC DRW 2WD	6.0L TD	17,400e/f
F-450 CCC DRW 2WD	6.0L TD	2,400f,t
F-450 CCC DRW 4WD	6.8L V-10	17,500f/g
F-450 CCC DRW 4WD	6.0L TD	17,100e/f
F-450 CCC DRW 4WD	6.0L TD	21,100f,t
F-550 CCC DRW 2WD	6.8L V-10	17,800f/g
F-550 CCC DRW 2WD	6.0L TD	17,400e/f
F-550 CCC DRW 2WD	6.0L TD	24,400f,t
F-550 CCC DRW 4WD	6.8L V-10	17,400f/g
F-550 CCC DRW 4WD	6.0L TD	17,000e/f
F-550 CCC DRW 4WD	6.0L TD	24,000f,t

**Note:** Weights shown for CCC models are for 176-inch wheelbase models. For 200-inch wheelbase models, weights may be somewhat less (usually 100 Lb with F-450/F-550).

## F-450/F-550 Chassis Cab Fifth-Wheel Towing, Manual Transmission

(Weights below assume 1,000-Lb second-unit body weight. Super Duty Chassis cab does not offer a fifth-wheel hitch as a factory-installed option).

Vehicle	Engine	Tow Limit (Lb)
F-450 RCC DRW 2WD	6.8L V-10	18,400f/g
F-450 RCC DRW 2WD	6.0L TD	18,000e/f
F-450 RCC DRW 2WD	6.0L TD	20,000f,t
F-450 RCC DRW 4WD	6.8L V-10	18,000f/g
F-450 RCC DRW 4WD	6.0L TD	17,600e/f
F-450 RCC DRW 4WD	6.0L TD	19,600f,t
F-550 RCC DRW 2WD	6.8L V-10	18,300f/g
F-550 RCC DRW 2WD	6.0L TD	17,900f
F-550 RCC DRW 2WD	6.0L TD	19,900f,t
F-550 RCC DRW 4WD	6.8L V-10	18,000f/g
F-550 RCC DRW 4WD	6.0L TD	17,600f
F-550 RCC DRW 4WD	6.0L TD	19,600f,t
F-450 SCC DRW 2WD	6.8L V-10	18,000f/g
F-450 SCC DRW 2WD	6.0L TD	17,600e/f
F-450 SCC DRW 2WD	6.0L TD	19,600f,t
F-450 SCC DRW 4WD	6.8L V-10	17,700f/g
F-450 SCC DRW 4WD	6.0L TD	17,300e/f
F-450 SCC DRW 4WD	6.0L TD	19,300f,t
F-550 SCC DRW 2WD	6.8L V-10	18,000f/g
F-550 SCC DRW 2WD	6.0L TD	17,500f
F-550 SCC DRW 2WD	6.0L TD	19,500f,t
F-550 SCC DRW 4WD	6.8L V-10	17,600f/g
F-550 SCC DRW 4WD	6.0L TD	17,200f
F-550 SCC DRW 4WD	6.0L TD	19,200f,t
F-450 CCC DRW 2WD	6.8L V-10	17,800f/g
F-450 CCC DRW 2WD	6.0L TD	17,400e/f
F-450 CCC DRW 2WD	6.0L TD	19,400f,t
F-450 CCC DRW 4WD	6.8L V-10	17,500f/g
F-450 CCC DRW 4WD	6.0L TD	17,100e/f
F-450 CCC DRW 4WD	6.0L TD	19,100f,t
F-550 CCC DRW 2WD	6.8L V-10	17,800f/g
F-550 CCC DRW 2WD	6.0L TD	17,300f
F-550 CCC DRW 2WD	6.0L TD	19,300f,t
F-550 CCC DRW 4WD	6.8L V-10	17,400f/g
F-550 CCC DRW 4WD	6.0L TD	17,000f
F-550 CCC DRW 4WD	6.0L TD	19,000f,t

**a**=3.31:1 axle ratio; **b**=3.55:1 axle ratio; **c**=3.73:1 axle ratio; **d**=4.10:1 axle ratio; **e**=4.30:1 axle ratio; **f**=4.88:1 axle ratio; **g**=5.38:1 axle ratio; **CC**=Crew Cab; **Ext**=Extended wheelbase; **SC**=SuperCab; **RCC**=Regular Chassis Cab; **SCC**=Super Chassis Cab; **CCC**=Crew Chassis Cab.

## Honda

Vehicle	Engine	Tow Limit (Lb)
Odyssey	3.5L V-6	3,500

Pilot	3.5L V-6	3,500/4,500*
Ridgeline	3.5L V-6	5,000

\*4,500-Lb rating for boats only.

## Hummer H1, H2, H2 SUT, H3

Vehicle	Engine	Tow Limit (Lb)
H1 Alpha 4-dr Open Top	6.6L TD	9,303
H1 Alpha 4-dr Wagon	6.6L TD	9,036
H2	6.0L V-8	6,700
H2 SUT	6.0L V-8	6,600
H3	3.5L I-5	4,500

## Hyundai

Vehicle	Engine	Tow Limit (Lb)
Santa Fe 2WD	2.7L V-6	2,700
Santa Fe 2WD	3.5L V-6	3,000
Santa Fe 4WD	2.7L V-6	2,200
Santa Fe 4WD	3.5L V-6	2,500
Tucson	2.7L V-6	2,000

## Infiniti

Vehicle	Engine	Tow Limit
QX56 2WD	5.6L V-8	9,000
QX56 AWD	5.6L V-8	8,900
FX	All	3,500

## Isuzu

Vehicle	Engine	Tow Limit (Lb)
Ascender 5-passenger, 2WD	4.2L I-6	5,300a
Ascender 5-passenger, 2WD	4.2L I-6	5,800b
Ascender 5-passenger, 4WD	4.2L I-6	5,200a
Ascender 5-passenger, 4WD	4.2L I-6	5,700b
Ascender 7-passenger, 2WD	4.2L I-6	4,900a
Ascender 7-passenger, 2WD	4.2L I-6	5,400b
Ascender 7-passenger, 2WD	5.3L V-8	5,900a
Ascender 7-passenger, 2WD	5.3L V-8	6,400b
Ascender 7-passenger, 4WD	4.2L I-6	4,700a
Ascender 7-passenger, 4WD	4.2L I-6	5,200b
Ascender 7-passenger, 4WD	5.3L V-8	5,700a
Ascender 7-passenger, 4WD	5.3L V-8	6,200b
i280 Ext Cab P/U	2.8L I-4	3,200
i350 Crew Cab P/U	3.5L I-5	4,000

**a**=3.73:1 axle ratio; **b**=4.10:1 axle ratio.

## Jeep

Vehicle	Engine	Tow Limit (Lb)
Commander 2WD	3.7L V-6	3,500a,c
Commander 2WD	4.7L V-8	6,500c
Commander 2WD	5.7L V-8	7,200c

# 2006 Towing Guide

Commander 4WD	3.7L V-6	3,500a
Commander 4WD	4.7L V-8	6,500c
Commander 4WD	5.7L V-8	7,200c
Grand Cherokee	3.7L V-6	3,500
Grand Cherokee	4.7L V-8	6,500
Grand Cherokee	5.7L V-8	7,200
Grand Cherokee SRT8	6.1 V-8	3,500
Liberty 2WD	2.4 I-4	2,000d
Liberty 2WD	3.7L V-6	3,500b
Liberty 2WD	3.7L V-6	5,000c
Liberty 4WD	2.4 I-4	2,000d
Liberty 4WD	3.7L V-6	3,500b
Liberty 4WD	3.7L V-6	5,000c
Wrangler	4.0L I-6	2,000

a=3.07:1 axle ratio; b=3.55:1 axle ratio; c=3.73:1 axle ratio; d=4.10:1 axle ratio.

## Kia

Vehicle	Engine	Tow Limit (Lb)
Sorento	3.5L V-6	3,500
Sportage	2.7L V-6	2,000

## Land Rover

Vehicle	Engine	Tow Limit (Lb)
Range Rover HSE	All	7,716
Range Rover Sport	All	7,716
LR3	All	7,700
Freelander	2.5L V-6	2,500

## Lexus

Vehicle	Engine	Tow Limit (Lb)
RX 330	3.3L V-6	3,500
RX 400h (hybrid)	3.3L V-6	3,500
GX 470	4.7L V-8	6,500
LX 470	4.7L V-8	6,500

## Lincoln-Mercury

Vehicle	Engine	Tow Limit (Lb)
Mark LT 2WD	5.4L V-8	8,900
Mark LT 4WD	5.4L V-8	8,600
Mariner	3.0L V-6	3,500t
Mountaineer 2WD 5 pass.	4.0L V-6	5,340
Mountaineer 2WD 5 pass.	4.6L V-8	7,240
Mountaineer AWD 5 pass.	4.0L V-6	5,160
Mountaineer AWD 5 pass.	4.6L V-8	7,060
Mountaineer 2WD 7 pass.	4.0L V-6	5,260
Mountaineer 2WD 7 pass.	4.6L V-8	7,160
Mountaineer AWD 7 pass.	4.0L V-6	5,100
Mountaineer AWD 7 pass.	4.6L V-8	6,980

Navigator 2WD	5.4L V-8	8,600
Navigator 4WD	5.4L V-8	8,300

## Mazda

Vehicle	Engine	Tow Limit (Lb)
B-2300 Reg Cab 2WD	2.3 I-4	2,260a,c
B-3000 Reg Cab 2WD	3.0L V-6	2,540m,c
B-3000 Reg Cab 2WD	3.0L V-6	2,480a,c
B-3000 Cab Plus 2WD	3.0L V-6	2,480m,b
B-3000 Cab Plus 2WD	3.0L V-6	2,440a,b
B-3000 Cab Plus 2WD	3.0L V-6	2,380m,c
B-3000 Cab Plus 2WD	3.0L V-6	2,340a,c
B-4000 4WD	4.0L V-6	3,120m,c
B-4000 4WD	4.0L V-6	5,580a,c
Tribute	3.0L V-6	3,500t

a=automatic transmission; b=3.73:1 axle ratio; c=4.10:1 axle ratio; m=manual transmission.

## Mercedes-Benz

Vehicle	Engine	Tow Limit (Lb)
G320	V-6	7,842
G500	V-8	7,842
G55 AMG	V-8	7,842
ML 350	V-6	7,842
ML 500	V-8	7,842
R-Class	All	4,705

## Mitsubishi

Vehicle	Engine	Tow Limit (Lb)
Endeavor	3.8L V-6	3,500t
Montero	3.8L V-6	5,000t
Raider Ext Cab 2WD	3.7L V-6	2,950m,b (1)
Raider Ext Cab 2WD	3.7L V-6	3,650m,c (1)
Raider Ext Cab 2WD	3.7L V-6	4,150a4,b (1)
Raider Ext Cab 2WD	3.7L V-6	4,450a4,d (1)
Raider Ext Cab 2WD	4.7L V-8	4,400m,b
Raider Ext Cab 2WD	4.7L V-8	4,800m,c
Raider Ext Cab 2WD	4.7L V-8	5,400a5,c (2)
Raider Ext Cab 2WD	4.7L V-8	6,600a5,d (2)
Raider Dbl Cab 2WD	3.7L V-6	4,050a4,c (1)
Raider Dbl Cab 2WD	3.7L V-6	4,350a4,d (1)
Raider Dbl Cab 2WD	4.7L V-8	5,300a5,c (2)
Raider Dbl Cab 2WD	4.7L V-8	6,500a5,d (2)
Raider Ext Cab 4WD	3.7L V-6	3,450m,c (3)
Raider Ext Cab 4WD	3.7L V-6	3,950a4,c
Raider Ext Cab 4WD	3.7L V-6	4,250a4,d (3)
Raider Ext Cab 4WD	4.7L V-6	4,700m,c
Raider Ext Cab 4WD	4.7L V-8	5,250a5,c
Raider Ext Cab 4WD	4.7L V-8	6,450a5,d (4)

Raider Dbl Cab 4WD	3.7L V-6	3,850a4,c
Raider Dbl Cab 4WD	3.7L V-6	4,150a4,d (3)
Raider Dbl Cab 4WD	4.7L V-8	5,100a5,c
Raider Dbl Cab 4WD	4.7L V-8	6,300a5,d (5)

**b**=3.21:1 axle ratio; **c**=3.55:1 axle ratio; **d**=3.92:1 axle ratio; **m**=manual transmission; **(1)**=Numbers shown are for base LS model. Similarly equipped DuroCross models tow 150 lb less. **(2)**=Numbers shown are for XLS model. Similarly equipped DuroCross model tows 150 lb less. **(3)**=Numbers shown are for base LS model. Similarly equipped DuroCross models tow 200-250 lb less. **(4)**=Number shown is for XLS model. Similarly equipped DuroCross model tows 250 lb less. **(5)**=Number shown is for XLS model. Similarly equipped DuroCross model tows 200 lb less.

## Nissan

Vehicle	Engine	Tow Limit (LB)
Armada 2WD	5.6L V-8	9,100
Armada 4WD	5.6L V-8	9,000
Frontier KC XE 2WD	2.5L I-4	3,500
Frontier KC SE, LE, Nismo 2WD	4.0L V-6	6,500
Frontier KC SE, LE, Nismo 4WD	4.0L V-6	6,300
Frontier CC SE, LE, Nismo 2WD	4.0L V-6	6,300
Frontier CC SE, LE, Nismo 4WD	4.0L V-6	6,100
Murano	3.5L V-6	3,500
Pathfinder	4.0L V-6	6,000
Quest	3.5L V-6	3,500
Titan KC	5.6L V-8	9,400
Titan CC	5.6L V-8	9,400
Xterra	4.0L V-6	5,000

**KC**=King Cab; **CC**=Crew Cab.

## Pontiac

Vehicle	Engine	Tow Limit (LB)
Montana	3.5L V-6	3,500t
Montana	3.9L V-6	NA
Torrent	3.4L V-6	3,500

## Porsche

Vehicle	Engine	Tow Limit (LB)
Cayenne	All	7,716

## Saab

Vehicle	Engine	Tow Limit (LB)
9-7X	4.2L I-6	5,600
9-7X	5.3L V-8	6,500

## Saturn

Vehicle	Engine	Tow Limit (LB)
Relay	All	3,500t
Vue	3.5L V-6	3,500

## Subaru

Vehicle	Engine	Tow Limit (LB)
B9 Tribeca	F-6	3500t
Forrester	F-4	2400

## Suzuki

Vehicle	Engine	Tow Limit (LB)
Grand Vitara	2.7L V-6	3,000
XL-7	2.7L V-6	3,000

## Toyota

Vehicle	Engine	Tow Limit (LB)
4Runner 2WD	4.0L V-6	6,700
4Runner 4WD	4.0L V-6	6,400
4Runner 2WD	4.7L V-8	7,300
4Runner 4WD	4.7L V-8	7,000
Highlander*	2.4L I-4	3,000
Highlander Hybrid*	3.3L V-6	3,500
Land Cruiser	4.7L V-8	6,500
Sienna*	3.3L V-6	3,500
Sequoia 2WD	4.7L V-8	6,500
Sequoia 4WD	4.7L V-8	6,200
Tacoma Reg Cab*	2.7L I-4	3,500
Tacoma Access Cab/X-Runner*	2.7L I-4	3,500
Tacoma Access Cab	4.0L V-6	6,500t
Tacoma Double Cab	4.0L V-6	6,500t
Tundra Reg Cab 2WD	4.0L V-6	5,000
Tundra Access Cab*	4.0L V-6	4,800
Tundra Reg Cab 2WD/4WD	4.7L V-8	7,100
Tundra Access Cab 2WD	4.7L V-8	7,100
Tundra Access Cab 4WD	4.7L V-8	6,900
Tundra Stepside 2WD	4.7L V-8	7,100
Tundra Stepside 4WD	4.7L V-8	6,900
Tundra Double Cab 2WD	4.7L V-8	6,800
Tundra Double Cab 4WD	4.7L V-8	6,500

Rating without towing package is 5,000 lb (unless noted by \*)

## Volkswagen

Vehicle	Engine	Tow Limit (LB)
Touareg	All	7,716

## Volvo

Vehicle	Engine	Tow Limit (LB)
S60	2.5L I-5	3,300
S80	2.5L I-5	3,300
V70	2.5L I-5	3,300
XC70	2.5L I-5	3,300
XC90	All	5,000